

EURO SEMI SYN-T RANGE

PREMIUM SEMI-SYNTHETIC ENGINE OIL - PARTICULATE FILTER SAFE

DESCRIPTION

EURO SEMI SYN-T is a range of advanced semi-synthetic passenger car engine oils formulated to meet the latest automotive performance standards, suitable for both petrol and diesel engines including those employing particulate filters.

EURO SEMI SYN-T provides total engine protection and excellent fuel economy with protection and performance beyond those possible with conventional motor oils.

EURO SEMI SYN-T responds exceptionally well to the demands of stop-and-go, city driving conditions. Its outstanding thermal stability, improved viscosity-temperature characteristics and excellent low temperature fluidity makes it a true all-season lubricant.

Specially selected synthetic and high performance conventional base stocks coupled with performance-enhancing additives provides superior cleaning power and wear protection, allowing EURO SEMI SYN-T products to meet both the rigors of cold weather operations as well some of the most demanding operating environments in tropical and desert regions.

SUMMARY OF BENEFITS

- DPF and GPF safe
- Excellent fuel economy
- Outstanding engine cleanliness
- Protects against rust and corrosion
- Extraordinary oxidation and thermal stability
- Exceptional low temperature performance
- True all-season lubricant
- Fully compatible with conventional (mineral) oils and other synthetic engine oils

PERFORMANCE STANDARDS

EURO SEMI SYN-T products are suitable for use where the following specifications are called for:

SAE GRADE	5W-30	5W-40
API SN	✓	✓
ACEA C2	✓	
ACEA C3	✓	✓
GM	Dexos 2	Dexos 2
MB	229.31	229.31
Porsche		A40
Renault		RN0700/ RN0710
DPF and GPF Safe	✓	✓

EURO SEMI SYN-T RANGE

PREMIUM SEMI-SYNTHETIC ENGINE OIL - PARTICULATE FILTER SAFE

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TYPICAL CHARACTERISTICS

EURO SEMI SYN-T	Test Method	Units	Typical Values	
			SAE 5W-30 #301145	SAE 5W-40 #301146
Density @ 15°C	ASTM D1298	kg/L	0.851	0.852
Colour	ASTM D1500		3.0	3.0
Kinematic Viscosity				
@ 40°C	ASTM D445	cSt	11.7	14.2
@ 100°C	ASTM D445	cSt	68.5	85.9
Viscosity Index	ASTM D2270	-	168	172
Apparent Viscosity @ -30°C	ASTM D5293	cP	5,800	6,100
Pour Point	ASTM D97	°C	-36	-36
Flash Point (COC)	ASTM D92	°C	218	222
Total Base Number	ASTM D2896	mgKOH/g	8.5	8.5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

301145 and 301146