

SYN-M 4T 100% SYNTHETIC 10W-40 API SN JASO MA2, PAO ESTER BLEND PREMIUM 100% SYNTHETIC MOTORCYCLE OIL

DESCRIPTION

Full Synthetic 4T Motorcycle Engine Oil 10W-40 is formulated using premium synthetic base oils, synthetic PAO & Esters coupled with an effective additive package for the ultimate protection of motorcycle engines. Full Synthetic 4T Motorcycle Engine Oil with PAO & Ester demonstrates excellent performance in the face of the increasing demands of motorcycle engines. Full Synthetic 4T Engine Oil with PAO & Ester is dyed a fluorescence yellow colour for easy identification.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

SPECIFICATIONS

Meets the following performance specifications:

- SAE 10W-40
- API SN
- JASO MA2

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au



SYN-M 4T 100% SYNTHETIC 10W-40 API SN JASO MA2, PAO ESTER BLEND PREMIUM 100% SYNTHETIC MOTORCYCLE OIL

TYPICAL CHARACTERISTICS

SAE VISCOSITY GRADE	10W-40
Density, kg/L@15°C	0.8591
Colour ASTM	Fluorescence Yellow
Kinematic Viscosity, mm2/s @ 40°C	92.87
Kinematic Viscosity, mm2/s @ 100°C	14.42
Viscosity Index	161
Apparent Viscosity @ -25°C, cP	5900
Pour Point, °C	-36
Flash Point COC, C	220
TBN, mg KOH/g	8.4

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

301122 (1L)

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au