



**SYN-M 4T PREMIUM SYNTHETIC 10W-40 API SL JASO MA2**  
**PREMIUM SYNTHETIC MOTORCYCLE OIL**

**DESCRIPTION**

Synthetic 4T Motorcycle Engine Oil 10W-40 is formulated using premium synthetic base oils coupled with an effective additive package for the protection of motorcycle engines. Synthetic 4T Motorcycle Engine Oil demonstrates excellent performance in the face of the increasing demands of motorcycle engines.

**SUMMARY OF BENEFITS**

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

**SPECIFICATIONS**

Meets the following performance specifications:

- SAE - 10W-40
- API - SL
- JASO - MA2

**STORAGE**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

**HEALTH, SAFETY AND ENVIRONMENT**

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.



**SYN-M 4T PREMIUM SYNTHETIC 10W-40 API SL JASO MA2**  
**PREMIUM SYNTHETIC MOTORCYCLE OIL**

**TYPICAL CHARACTERISTICS**

SAE VISCOSITY GRADE	10W-40
Density, kg/L @ 15°C	0.870
Colour ASTM	Fluorescence Yellow
Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C	100.1
Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C	14.3
Viscosity Index	147
Apparent Viscosity @ -25°C, cP	6200
Pour Point, °C	-33
Flash Point COC, C	234
TBN, mg KOH/g	5.6

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**AVAILABLE PACK SIZES**

30.8121 (0.8L), 301121 (1L)