



SYN-M 4T PREMIUM SYNTHETIC 10W-40 API SL JASO MB
PREMIUM SYNTHETIC SCOOTER OIL

DESCRIPTION

4T Scooter engine oil is formulated from premium synthetic base oils coupled with an effective additive package for the protection of scooter engines. 4T Scooter Engine Oil demonstrates excellent performance in the face of increasing demands of scooter engines.

Suitable for use in 4-stroke scooter engines requiring and API SL (or earlier) and JASO MB oil.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

SPECIFICATIONS

Meets the following performance specifications:

- SAE - 10W-40
- API - SL
- JASO - MB

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.



SYN-M 4T PREMIUM SYNTHETIC 10W-40 API SL JASO MB
PREMIUM SYNTHETIC SCOOTER OIL

TYPICAL CHARACTERISTICS

SAE VISCOSITY GRADE	10W-40
Density, kg/L @ 15°C	0.870
Colour ASTM	Fluorescence Yellow
Kinematic Viscosity, mm ² /s @ 40°C	100.5
Kinematic Viscosity, mm ² /s @ 100°C	14.8
Viscosity Index	153
Apparent Viscosity @ -25°C, cP	5900
Pour Point, °C	-33
Flash Point COC, C	230
TBN, mg KOH/g	5.6

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

30.8123 (0.8L)