

SYN-X 3000 5W-20

PREMIUM SEMI-SYNTHETIC GASOLINE ENGINE OIL

DESCRIPTION

SYN-X 3000 5W-20 is an advanced semi-synthetic passenger car gasoline engine oil formulated to meet the latest automotive performance standards. SYN-X 3000 5W-20 provides total engine protection and excellent fuel economy in today's advanced fuel efficient engines including hybrids.

SYN-X 3000 5W-20 exceeds the latest API SP gasoline engine performance standard and fully meets the fuel economy and performance requirements of ILSAC GF-6A to meet the needs of today's modern engines. Particularly suited to modern stop-start driving conditions.

SUMMARY OF BENEFITS

- Exceptional fuel economy
- Outstanding engine cleanliness
- Protects against rust and corrosion
- Extraordinary oxidation and thermal stability
- Exceptional low temperature performance
- Enhanced shear stability for stay-in-grade over the complete service interval
- Fully compatible with conventional (mineral) oils and other synthetic engine oils

SPECIFICATIONS

SYN-X 3000 5W-20 meets the following specifications:

- SAE 5W-20
- API SP
- ILSAC GF-6A
- Ford M2C 945A
- Chrysler MS 6395
- GM 6094M

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

SYN-X 3000 5W-20

PREMIUM SEMI-SYNTHETIC GASOLINE ENGINE OIL

TYPICAL CHARACTERISTICS

| SYN-X 3000 5W-20 | Test Method | Units | Results |
|----------------------------|-------------|---------|---------|
| Density @ 15°C | ASTM D1298 | kg/L | 0.845 |
| Colour | ASTM D1500 | - | 3.0 |
| Kinematic Viscosity | | | |
| @ 40°C | ASTM D445 | cSt | 48.4 |
| @ 100°C | ASTM D445 | cSt | 8.29 |
| Viscosity Index | ASTM D2270 | - | 146 |
| Apparent Viscosity @ -30°C | ASTM D5293 | cP | 5,975 |
| Pour Point | ASTM D97 | °C | -36 |
| Flash Point (COC) | ASTM D92 | °C | 212 |
| Total Base Number | ASTM D2896 | mgKOH/g | 7.5 |

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

300149