



**GULF WESTERN OIL**  
THE TOUGH AUSTRALIAN

# TRANSYN-MF LV

**HIGH QUALITY MULTI FUNCTIONAL AUTOMATIC TRANSMISSION FLUID**

## DESCRIPTION

Transyn-MF LV is a synthetic blend multi functional Automatic Transmission Fluid. It meets the requirements of a wide range of American, Japanese and European OEM's.

Transyn-MF LV is a mid-tier ATF and is does not meet some of the OEM requirements of SYN-TS, most notably 6 Speed ZF transmissions that require a fluid meeting ZF-TE-ML-09.

**Note:** The below is a summary only, for more details please contact Gulf Western Oil Technical.

## SUMMARY OF BENEFITS

- Synthetic blend
- Suitable for extended drain intervals where standard Dexron III mineral oils are required
- Reduces the need to stock additional fluids
- Friction modied formulation
- High VI, Shear stable blend that oers excellent cold start ow properties
- Ideal for heavy duty applications such as towing and long distance driving in very hot or cold climates
- Can be used where a Dexron IID, III, IIIE, VI, Ford 95LE, ATF+4, SPIII and C4 fluids are called for

## SPECIFICATIONS

Transyn-MF LV meets the following international performance specifications:

- Dexron III
- ATF+3,+4
- ATF JWS 3309
- Allison TES295, 389
- Chrysler AS68RC, SP-III
- Mercedes Benz 236.1, 236.11, 236.12, 236.14, 236.15, 236.3, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9 & 236.91
- Ford WSS-M2C922-A1
- TYPE A Suffix
- Honda DW-1, Z-1
- Hyundai/Kia Genuine, 1K, JWS 3309, NWS 9638 T-5
- Isuzu Genuine ATF

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

**Head Office:** 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

**Phone:** 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

**ACN:** 087 558 398



**GULF WESTERN OIL**  
THE TOUGH AUSTRALIAN

PRODUCT DATA SHEET

# TRANSYN-MF LV

HIGH QUALITY MULTI FUNCTIONAL AUTOMATIC TRANSMISSION FLUID

## SPECIFICATIONS (CONTINUED)

- Jaguar Fluid 8432, JLM 20238, 20292, 21044, K17
- Land Rover TYK500050
- MAN 339A
- Maserati 231603
- Mazda F1, FZ, JWS3317, M5, MIII, T-IV
- Mitsubishi J2, J3, SPII/III
- Nissan Matic D, J, K, S, W
- Porsche 043 204 41, 205 09, 205 28, 304 00, 999 917 547 00 (A2)
- Renault Matic D2
- SAAB 3309 T-IV, 93 165 147 - AW1
- Subaru HP
- Suzuki 3314, 3317
- Toyota/Lexus DII, T, T-III, T IV
- VW/Audi 052 - 025A2, 055, 162, 533, 990, 055 005, 025, 540, 000 162
- Volvo PN 1161521, 1161540/1161640
- ZF TE-ML 11A, TE-ML-11B

## STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

**Head Office:** 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

**Phone:** 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

**ACN:** 087 558 398



**GULF WESTERN OIL**  
THE TOUGH AUSTRALIAN

# TRANSYN-MF LV

HIGH QUALITY MULTI FUNCTIONAL AUTOMATIC TRANSMISSION FLUID

## TYPICAL CHARACTERISTICS

TRANSYN-MF LV	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.855
Kinematic Viscosity @ 40°C	ASTM D445	cSt	31
@ 100°C	ASTM D445	cSt	6.4
Viscosity Index	ASTM D2270	-	165
Pour Point	ASTM D97	°C	-42
Flash Point (COC)	ASTM D92	°C	224

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## AVAILABLE PACK SIZES

318142 -18L

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

**Head Office:** 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

**Phone:** 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

**ACN:** 087 558 398