



GULF WESTERN OIL
GO THE DISTANCE

SYN-X 6000 5W-50

PREMIUM FULL SYNTHETIC GASOLINE ENGINE OIL

DESCRIPTION

Syn-X 6000 5W-50 is an advanced, premium full synthetic passenger car engine oil formulated to meet the demands high performance gasoline powered vehicles including those driven in a spirited manner. Syn-X 6000 5W-50 provides total engine protection with exceptionally high levels of performance, viscosity control and and protection beyond the limits of conventional oils.

Syn-X 6000 5W-50 responds exceptionally well to the demands of frequent stop-and-go, city driving conditions or a day on the race track. Its outstanding thermal stability, improved viscosity-temperature characteristics and excellent low temperature fluidity makes it a true all-season lubricant.

Syn-X 6000 5W-50 is designed to protect today's modern, high performance gasoline powered engines including turbo charged and super charged engines.

SUMMARY OF BENEFITS

- Outstanding engine cleanliness resulting in less power robbing sludge and deposit build up in the engine
- Protects against rust and corrosion
- Excellent oxidative and thermal stability
- Exceptional high and low temperature performance. True all-season lubricant
- Fully compatible with conventional (mineral) oils and other synthetic engine oils
- Protects against LSPI

SPECIFICATIONS

Syn-X 6000 5W-50 meets the following international performance specifications:

- API SP/CF
- ACEA A3/B4
- MB 229.3, 229.1
- Porsche A40

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398



GULF WESTERN OIL
GO THE DISTANCE

PRODUCT DATA SHEET

SYN-X 6000 5W-50

PREMIUM FULL SYNTHETIC GASOLINE ENGINE OIL

TYPICAL CHARACTERISTICS

SYN-X 6000 5W-50	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.853
Colour	ASTM D1500		3.0
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	108.6
@ 100°C	ASTM D445	cSt	17.7
Viscosity Index	ASTM D2270	-	181
Apparent Viscosity @ -30°C	ASTM D5293	cP	5,600
Pour Point	ASTM D97	°C	-39
Flash Point (COC)	ASTM D92	°C	222
Total Base Number	ASTM D2896	mgKOH/g	11.3

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

4L - 304353, 1L - 301353

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747

Phone: 02 9673 9600 - **Fax:** 02 9623 6466 - **Email:** sales@gulfwestern.com.au - **Web:** www.gulfwestern.com.au

ACN: 087 558 398