

TECHNICAL DATA SHEET

TRANSYN-MF LV



DESCRIPTION

Transyn-MF LV is a synthetic blend multi functional Automatic Transmission Fluid. It meets the requirements of a wide range of American, Japanese and European OEM's. Transyn-MF LV is a mid-tier ATF and does not meet some of the OEM requirements of SYN-TS, most notably 6 Speed ZF transmissions that require a fluid meeting ZF-TE-ML-09. Note: The below is a summary only, for more details please contact Gulf Western Oil Technical.

SUMMARY OF BENEFITS

- Synthetic blend
- Suitable for extended drain intervals where standard DX-3 mineral oils are required
- Reduces the need to stock additional fluids
- Friction modied formulation
- High VI, Shear stable blend that offers excellent cold start ow properties
- Ideal for heavy duty applications such as towing and long distance driving in very hot or cold climates
- Can be used where a DX-2, DX-3 or DX-6, Ford 95LE, ATF+4, SPIII and C4 fluids are called for

SPECIFICATIONS

- DX-3
- ATF+3,+4
- ATF JWS 3309
- ALLISON TES295, 389
- CHRYSLER AS68RC, SP-III
- MERCEDES BENZ 236.1, 236.11,236.12, 236.14, 236.15, 236.3, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9 & 236.91
- FORD WSS-M2C922-A1
- TYPE A SUFFIX
- HONDA DW-1, Z-1
- HYUNDAI/KIA GENUINE, 1K, JWS 3309, NWS 9638 T-5
- ISUZU GENUINE ATF
- JAGUAR FLUID 8432, JLM 20238, 20292, 21044, K17
- LAND ROVER TYK500050
- MAN 339A
- MASERATI 231603
- MAZDA F1, FZ, JWS3317, M5, MIII, T-IV
- MITSUBISHI J2, J3, SPII/III
- NISSAN MATIC D, J, K, S, W
- PORSCHE 043 204 41, 205 09, 205 28, 304 00, 999 917 547 00 (A2)
- RENAULT MATIC D2
- SAAB 3309 T-IV, 93 165 147 - AW1
- SUBARU HP
- SUZUKI 3314, 3317
- TOYOTA/LEXUS DII, T, T-III, T IV
- VW/AUDI 052 - 025A2, 055, 162, 533, 990, 055 005, 025, 540, 000 162
- VOLVO PN 1161521, 1161540/1161640
- ZF TE-ML 11A, TE-ML-11B

TRANSYN-MF LV	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.855
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	31
@ 100°C	ASTM D445	cSt	6.4
VISCOSITY INDEX	ASTM D2270	-	165
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°C	224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

18LT - #318142

June 2022

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au