

DESCRIPTION

OUTBOARD FC-W 25W-40 is a dedicated synthetic small engine oil meeting the NMMA FC-W performance standard and has been specifically formulated to meet the demands of modern 4 Stroke Outboard Engines. Suitable for use in many makes and model of 4 Stroke Outboard Engines from manufacturers such as: Chrysler, Evinrude, Johnson, Mercury, Suzuki and Yamaha.

SUMMARY OF BENEFITS

- Outstanding protection for seasonally used equipment
- Reduces corrosion from water entrapment in the oil
- Prevention of ring sticking and wear
- Excellent control of engine deposits leading to superb engine cleanliness
- Improved lubricity which is important for engines operating at high speeds for sustained periods of time
- Meeting JASO MA also makes this oil suitable for use in motorcycles with a wet clutch
- Optimised phosphorus level to protect catalytic converters

SPECIFICATIONS

- NMMA FC-W (CAT)
- API SM
- JASO MA2

SUITABLE FOR



OUTBOARD FC-W 25W-40	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.871
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	135
@ 100°C	ASTM D445	cSt	14.5
APPARENT VISCOSITY @ -25°C	ASTM D5293	cP	85,00
VISCOSITY INDEX	ASTM D2270	-	107
POUR POINT	ASTM D97	°C	-18
FLASH POINT (COC)	ASTM D92	°C	>220
TOTAL BASE NUMEBR	ASTM 2896	mgKOH/g	8
SULPHATED ASH	ASTM D874	% mass	0.9%

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

#304110S

April 2023