

# OUTBOARD FOUR STROKE OIL

SEMI-SYNTHETIC, API SG, 10W-40, FC-W

## DESCRIPTION

Outboard Four Stroke Oil is a semi-synthetic high performance engine oil for use in water-cooled Four-stroke outboard motors calling for a 10W-40 API FC-W specification. It is approved for API FC-W requirements.

### SUMMARY OF BENEFITS

- Suitable for FC-W requirements
- Formulated using severely refined mineral oils to give excellent protection against engine wear for prolonged engine life

### SPECIFICATIONS

Outboard Four Stroke meets the following international performance specifications:

- NMMA FC-W
- API SG
- 10W-40 Viscosity
- JASO MA (T903:2006)

Meets the warranty requirements of:  
Mercury, Johnson, Evinrude, Yamaha,  
Mariner, Force, Suzuki, Tohatsu and any  
other engine requiring FC-W performance

## STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

# OUTBOARD FOUR STROKE OIL

SEMI-SYNTHETIC, API SG, 10W-40, FC-W

## TYPICAL CHARACTERISTICS

OUTBOARD FOUR STROKE	Test Method	Units	Results
Density @ 15°C	ASTM D7042	kg/L	0.8610
Kinematic Viscosity @ 40°C	ASTM D7042	cSt	100
@ 100°C	ASTM D7042	cSt	15
Total Base Number	FTIR	mgKOH/g	>5

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## AVAILABLE PACK SIZES

5lt - 60582