

SCOOTER 4T 10W-40 SL

PREMIUM SCOOTER ENGINE OIL

DESCRIPTION

4T Scooter Engine Oil is formulated from premium base oils coupled with a highly effective additive package for the protection of scooter engines and optimal transmission operation. 4T Scooter Engine Oil demonstrates excellent performance in the face of increasing demands of scooter engines.

Suitable for use in 4-stroke scooter engines requiring an API SL (or earlier) and JASO MB oil.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear
- Correct frictional characteristics for optimal transmission operation
- Shear stable formulation offering enhanced protection across the full oil drain

SPECIFICATIONS

Meets the following performance specifications:

- SAE - 10W-40
- API - SL
- JASO - MB

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

SCOOTER 4T 10W-40 SL

PREMIUM SCOOTER ENGINE OIL

TYPICAL CHARACTERISTICS

SCOOTER 4T 10W-40 SL	Test Method	Units	Results
Colour (visual)	-	-	Fluorescent yellow
Odour/Fragrance	-	-	Strawberry
Density @ 15°C	ASTM D7042	kg/L	0.864
Colour	ASTM D1500	-	2.0
Kinematic Viscosity @ 40°C	ASTM D7042	cSt	103.2
Kinematic Viscosity, mm ² /s @ 100°C	ASTM D7042	cSt	14.4
Viscosity Index	ASTM D2270	-	144
Apparent Viscosity @ -25°C	ASTM D5293	cP	5900
Pour Point	ASTM D97	°C	-33
Flash Point (COC)	ASTM D92	°C	226
Total Base Number	ASTM D2896	mg KOH/g	5.8

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

300153