

SYN-STAR LV 0W-20

FULL SYNTHETIC, API SP ILSAC GF-6 RESOURCE CONSERVING

DESCRIPTION

Syn-Star LV 0W-20 is a full synthetic specially engineered low viscosity high performance passenger car lubricant suitable for late model, low emission passenger motor vehicles including hybrids.

Syn-Star LV 0W-20 can be used where fuel economy oils are specified such as Toyota, Subaru, Jeep, Honda and Hyundai vehicles calling for a 0W-20 or 5W-20 petrol engine oil. Excellent cold flow characteristics whilst maintaining high levels of wear protection and cleaning ability even in severe stop-start driving conditions. Formulated to meet API SP requirements and ILSAC GF-6 Resource Conserving.

SUMMARY OF BENEFITS

- Synthetic formulation
- Super extended drain intervals surpassing any mineral based lubricants
- Excellent control of combustion products resulting in cleaner engines
- Reduces fuel consumption due to superior technology and low viscosity formulation
- Outstanding low temperature viscometrics for reduced wear at start up
- Suitable for European, American and Asian engines calling for a low viscosity 0W-20 or 5W-20 engine oil

SPECIFICATIONS

Syn-Star LV 0W-20 meets the following international performance specifications:

- SAE 0W-20
- API SP, SN Plus, SN
- ILSAC GF-6, GF-5, GF-4
- Chrysler MS-6395
- Ford M2C947-A

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

SYN-STAR LV 0W-20

FULL SYNTHETIC, API SP ILSAC GF-6 RESOURCE CONSERVING

TYPICAL CHARACTERISTICS

SYN-STAR LV 0W-20	Test Method	Units	Results
Density @ 15°C	ASTM D1298	kg/L	0.846
Kinematic Viscosity @ 40°C	ASTM D445	cSt	44
@ 100°C	ASTM D445	cSt	8.3
Viscosity Index	ASTM D2270	-	>165
Pour Point	ASTM D97	°C	-39
Flash Point (COC)	ASTM D92	°C	200
Total Base Number	ASTM D2896	mgKOH/g	7.3
Sulphated Ash	ASTM D874	% mass	0.8

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

301134 - 1L, 304134 - 4L