

TECHNICAL DATA SHEET

TOP DOG CK-4 RANGE



DESCRIPTION

Top Dog CK-4 is a premium diesel engine oil using the latest in lubrication technology and is ideally suited for mixed fleets including American, European and Japanese diesel engines. It can be used in a range of applications from stationary engines, late model petrol engines and light diesels up to heavy duty earth moving and road transport applications.

SUMMARY OF BENEFITS

- Extended drain intervals for more up time
- Reduced oil consumption
- Greatly reduced engine wear giving extended engine life
- Formulated for engines fitted with Exhaust Gas Recirculation (EGR), Diesel Particulate Filters (DPF) and AdBlue (SCR) systems
- Superior sludge and soot control for a cleaner engine
- Very good low temperature viscometrics for reduced wear at start up
- Enhanced viscosity retention through use of highly shear stable viscosity modifiers

SPECIFICATIONS

- API CK-4
- ACEA E7/E11
- DTFR 15C100
(FORMERLY MB-APPROVAL 228.31)
- MAN M 3775
- MTU OIL CATEGORY 2.1
- VOLVO VDS 4.5
- MACK EOS 4.5
- RENAULT RLD-4
- FORD WSS M2C171-F1
- DEUTZ DQC III-18 LA
- DETROIT DIESEL DFS 93K222
- CUMMINS CES 20086
- CATERPILLAR ECF-3
- ALLISON TES-439
- JASO DH-2

SUITABLE FOR



TOP DOG CK-4 RANGE	TEST METHOD	UNITS	10W-30	10W-40	15W-40
DENSITY @ 15°C	ASTM D1298	kg/L	0.867	0.851	0.870
KINEMATIC VISCOSITY					
@ 40°C	ASTM D445	cSt	82.7	105.9	114
@ 100°C	ASTM D445	cSt	12.2	15.2	15.2
VISCOSITY INDEX	ASTM D2270	-	140	151	139
APPARENT VISCOSITY AT -20°C	ASTM D5293	cP	-	6400	5500
FLASH POINT (COC)	ASTM D92	°C	>230	>230	>230
POUR POINT	ASTM D6749	°C	-48	-42	-42
SULPHATED ASH	ASTM D874	% mass	0.98	0.98	0.98
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	9.6	10.4	9.5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

Sep 2024

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au