

DESCRIPTION

4T Scooter Engine Oil is formulated from premium base oils coupled with a highly effective additive package for the protection of scooter engines and optimal transmission operation. 4T Scooter Engine Oil demonstrates excellent performance in the face of increasing demands of scooter engines. Suitable for use in 4-stroke scooter engines requiring an API SN (or earlier) and JASO MB oil.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear
- Correct frictional characteristics for optimal transmission operation
- Shear stable formulation offering enhanced protection across the full oil drain

SPECIFICATIONS

- SAE - 10W-40
- API - SN
- JASO - MB

SCOOTER 4T 10W-40 SN	TEST METHOD	UNITS	RESULTS
COLOUR (VISUAL)	-	-	Fluorescent yellow
ODOUR/FRAGRANCE	-	-	Strawberry
DENSITY @ 15°C	ASTM D1298	kg/L	0.864
COLOUR	ATSM D1500	-	2.0
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	103.2
@ 100°C	ASTM D445	cSt	14.4
VISCOSITY INDEX	ASTM D2270	-	144
APPARENT VISCOSITY @ -25°C	ASTM D5293	cP	5,900
POUR POINT	ASTM D97	°C	-33
FLASH POINT (COC)	ASTM D92	°C	226
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	8.4

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

#30.8153

February 2022