

# TECHNICAL DATA SHEET

# TACWAY SLIDEWAY OIL



## DESCRIPTION

Tacky, extreme pressure anti-wear machine tool slideway oil. Contains antiwear additives and tackifiers to protect the tool and minimise "run-off". Available in ISO viscosity grades 32 and 68.

## SUMMARY OF BENEFITS

- Anti Corrosive
- High level of protection with its EP properties
- Provides good anti-rust and storage protection
- Good surface coating characteristics

## SPECIFICATIONS

- CINCINATTI MACHINE
- GM LS EP 2
- AGMA 9005-E02
- ISO 12925-1 CKC/CKD
- DIN 51517 (3)
- US STEEL 224

TACWAY SLIDEWAY OIL	TEST METHOD	UNITS	32	68
DENSITY @ 15°C	ASTM D1298	kg/L	0.853	0.886
KINEMATIC VISCOSITY				
@ 40°C	ASTM D445	cSt	32	68
@ 100°C	ASTM D445	cSt	6.1	8.6
VISCOSITY INDEX	ASTM D2270	-	130	97
POUR POINT	ASTM D97	°C	-30	-12
FLASH POINT (COC)	ASTM D92	°C	204	218

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

## STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

## AVAILABLE PACK SIZES

32: IBC - #300049B, 205LT - #300049

68: IBC - #30073B, 205LT - #30073, 20LT - #32073

September 2022

**GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD**

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747  
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au