

CHASSIS GREASE CH RANGE

CALCIUM SOAP CHASSIS AND GENERAL LUBRICATION GREASE

DESCRIPTION

CHASSIS GREASE CH products are a range of high quality, general purpose greases suitable for a range lubrication applications. These adhesive and water resistant greases offer cost effective lubrication where application speed and temperatures are low to moderate.

CHASSIS GREASE CH products have a high resistance to water wash out and cling firmly to moving parts such as ball joints, chassis and U-joints and are suitable for use with manual lubrication or automated lubrication systems.

Suitable for a wide range of vehicular applications including tractors, trucks, earthmoving equipment and passenger vehicles.

SUMMARY OF BENEFITS

- Highly resistant to water wash off and providing high levels of corrosion resistance
- Allows effective lubrication even in damp environments
- Excellent clingability - stays put in application
- High mechanical stability - resists mechanical shearing offering longer lubricant life
- No heavy metals or other toxic or hazardous components
- Safe for use in applications where copper and its alloys (yellow metals) are used

SPECIFICATIONS

HCHASSIS GREASE CH Products: meets the following specifications:

- NLGI Grade 1, 2 and 3 as per requirement
- Operating temperature range: -10 to 70°C

STORAGE

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

CHASSIS GREASE CH RANGE

CALCIUM SOAP CHASSIS AND GENERAL LUBRICATION GREASE

TYPICAL CHARACTERISTICS

NLGI GRADE	1	2	3
Appearance	Green & Tacky	Green & Tacky	Green & Tacky
Worked Penetration @25°C, 1/10mm, 60 strokes	321	282	237
Dropping Point, °C	102	102	102
Rust Prevention	Pass	Pass	Pass
Copper Strip Corrosion	1b	1b	1b
Base Oil Viscosity at 100°C, cSt	20	20	20

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

CHASSIS GREASE CH1 - 300161 (180kg drum), 315161 (15kg pail)

CHASSIS GREASE CH2 - 300162 (180kg drum), 315162 (15kg pail)

CHASSIS GREASE CH3 - 300163 (180kg drum), 315163 (15kg pail)