



**DESCRIPTION**

Syn-TS® MV is a technically advanced, full synthetic multi-vehicle automatic transmission fluid suitable for use as service fill in most step-type automatic transmission applications. Proven performance through extensive field and laboratory testing to provide a service fill alternative to OEM fluids from US, European and Asian transmission manufacturers.

**SUMMARY OF BENEFITS**

- Eliminates the need to stock many OEM fluids
- Full Synthetic formulation offering enhanced temperature-viscosity characteristics and longer life
- Superior, shear stable formulation for enhanced performance and smooth shifting throughout the fluid life
- Proven wear protection to enhance transmission life
- Excellent anti-shudder performance
- Improved sludge and varnish control
- Extended drain intervals may be possible
- Suited to both current and older automatic transmissions

**SPECIFICATIONS**

- DEXRON VI (BACKWARDS COMPATIBLE DEXRON III)
- MERCON LV
- CHRYSLER ATF +4
- JASO 1-A AND 1-A-LV
- AISIN WARNER AW-1
- HONDA DW-1
- HYUNDAI/KIA SP-IV, SPH-IV, SP-IV RR
- MITSUBISHI ATF-J2, SP-IV
- NISSAN MATIC S
- TOYOTA WS (JWS 3324)
- AUDI/VW G 055 005, G 055 162, G 060 162, G 055 540
- BMW 83 22 0 142516, 83 22 2 152 426 ZF 6, 8 AND 9 SPEED TRANSMISSIONS

SYN-TS MV	TEST METHOD	UNITS	RESULTS
APPEARANCE	Visual	-	Red, mobile fluid
DENSITY @ 15°C	ASTM D1298	Kg/L	0.846
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	37
@ 100°C	ASTM D445	cSt	6.7
VISCOSITY INDEX	ASTM D2270	-	140
BROOKFIELD VISCOSITY @ -40°C	ASTM D2983	mPa.s	10,600
POUR POINT	ASTM D97	°C	-45
FLASH POINT (COC)	ASTM D92	°C	180 min

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

1000LT - #300356B