

**DESCRIPTION**

Turbo Diesel LA 15W-40 is a versatile engine oil for diesel engines requiring API CF-4/SG performance or earlier performance standards. Turbo Diesel LA 15W-40 is suitable for diesel, LPG and petrol engines, operating on or off highway. Suitable for a wide range of naturally aspirated and turbo charged heavy duty diesel engines with excellent protection of key engine components including turbo chargers. Not to be used in 2 Stroke Diesel Engines requiring API CF-II specification. Use Turbo SAE 30 or Turbo SAE 40 in those applications.

**SUMMARY OF BENEFITS**

- Turbo Diesel LA 15W-40 meets the API CF-4/SG performance requirements, offering cost efficient rationalisation for some mixed fleets
- Excellent soot and sludge control reducing the oil’s likelihood to thicken in operation
- High levels of protection against engine wear
- Robust reserve alkalinity (TBN) protects against acidic combustion components throughout the oil service interval
- Excellent, stay-in-grade performance ensure viscosity integrity and reduced oil consumption across the drain interval
- High shear stability enables use of Turbo Diesel LA 15W-40 in some hydraulic and transmission applications
- Excellent performance in mobile equipment gas engine applications

**SPECIFICATIONS**

- SAE 15W-40
- API CF-4/SG
- MB 227.1
- CATERPILLAR TO-2
- ALLISON C-4

TURBOIL DIESEL LA	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.872
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	117
@ 100°C	ASTM D445	cSt	15.2
VISCOSITY INDEX	ASTM D2270	-	135
APPARENT VISCOSITY @ -20°C	ASTM D5293	cP	6250
POUR POINT	ASTM D97	°C	-36
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	8
SULPHATED ASH	ASTM D874	% mass	<1.00

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

1LT - #30102, 4LT - #30402