



DESCRIPTION

Air-Cooled 2-stroke full synthetic quality engine oil meeting the demand of modern engines and suitable for E-TEC technology engine; High performance low ash oil for Air-Cooled 2-stroke motors formulated for both oil injected and pre-mixed systems. Recommended for 2-stroke lawnmowers, chainsaws, brush cutters, motorbikes, and other similar 2-stroke applications. Air-Cooled 2-stroke full synthetic meets the requirement of the full range of low ash 2-stroke oil specifications from JASO FB and ISO-L-EGB to JASO FD & ISO-L-EGD quality levels.

Note: Not suitable for use in outboard marine engines that call for a NMMA TCW 3. Please refer to manufacturer recommendations for correct mixing/blending ratio.

SUMMARY OF BENEFITS

- Suitable for API TA, TB, TC requirements
- Low ash formulation controls piston, port and plug cleanliness
- Contains a diluent to aid mixing with leaded and unleaded petrol
- Synthetic formulation

SPECIFICATIONS

- API TC
- JASO FC, FB
- TISI

RECOMMENDATIONS

Snowmobiles:

- Bombardier (BRP)
- Polaris
- Arctic Cat
- Yamaha

Lawn Maintenance/ Forestry Equipment:

- Hitachi
- Honda
- John Deere
- Kawasaki
- Lawn Boy
- Massey Ferguson
- Polaris
- Husqvarna
- Poulan

Powermate (formerly Coleman)

- Tecumseh
- Weedeater
- Woods
- Yamaha
- Yardman
- Stihl
- Dolmar

Small CC Motorcycles and Scooters:

- Yamaha
- TVS
- Bombardier (BRP)
- Honda
- Kawasaki

TECHNICAL DATA SHEET

TWO STROKE AIR-COOLED FULL SYNTHETIC



SUITABLE FOR



TWO STROKE - AIR COOLED FULL SYNTHETIC	TEST METHOD	UNITS	RESULTS
DENSITY @ 30°C	ASTM D4052	kg/L	0.844
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	31.86
@ 100°C	ASTM D445	cSt	6
TBN	ASTM D2896	Mg KOH/g	>1.1
VISCOSITY INDEX	ASTM D2270	-	145
FLASH POINT (COC)	ASTM D92	°C	90
POUR POINT	ASTM D97	°C	-30/-48
COLOUR, ASTM	ASTM D1500	-	BLUE/GREEN

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

11LT - # 301268SD, 4L – 304268SD (-30/GREEN), 1LT - # 301268S, 4L – 304268S (-48/BLUE)

OCT 2023