

**DESCRIPTION**

POWER ARCTIC 4T 0W-40 is an advanced, full PAO and Ester synthetic engine lubricant designed to meet the special operating conditions of Snowmobiles, All Terrain Vehicles, Utility Terrain Vehicles and other 4 stroke power equipment operating in severe cold environments.

Compatible with leaded and unleaded gasolines, biofuels and other specialised fuels used in 4 stroke engines operating in harsh arctic conditions. POWER ARCTIC 4T 0W-40 will continue to flow and protect where ordinary oils will not flow or protect equipment. The product is recommended for snowmobiles, ATV's and other powersports, racing applications that require 0W-40 oil, including Polaris, Honda, Yamaha, Suzuki, Kawasaki, BRP, Arctic Cat and other modern four-stroke engines.

**SUMMARY OF BENEFITS**

- Enhanced frictional properties from the full synthetic formulation result in improved fuel economy and extended engine life
- Enhanced cold flow at start up offering superior protection in extreme cold including polar environments
- Superior corrosion protection by neutralization of water and other contaminants
- Excellent viscosity retention across full drain interval offering optimized protection
- Superior oxidation and thermal stability for extended oil drain interval capability
- Excellent engine protection at high rev and high engine temperatures such as in race conditions
- Excellent frictional performance for improved clutch durability
- Will not impact operation of catalytic converters

**SPECIFICATIONS**

- SAE 0W-40
- API SN
- JASO MA2

POWER ARCTIC 4T 0W-40	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D4052	kg/L	0.858
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	75.4
@ 100°C	ASTM D445	cSt	14.4
VISCOSITY INDEX	ASTM D2270	-	200
APPARENT VISCOSITY @ -35°C	ASTM D5293	cP	3035
COLOUR	ASTM D1500	-	< 3.5
POUR POINT	ASTM D97	°C	-60
FLASH POINT (COC)	ASTM D92	°C	210
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	7
SULPHATED ASH	ASTM D874	% mass	0.75

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

#301272 - 1LT

October 2023