

**DESCRIPTION**

Gulf Western Ultra Clear LS 75W-140 is a full synthetic high performance extreme pressure lubricant recommended for hypoid or spiral bevel axles, gears and steering boxes of automotive equipment. With limited slip additive included it is suitable for almost all heavily loaded differentials.

Gulf Western Ultra Clear LS 75W-140 is suitable to use where SAE 140, SAE 80W-140 and SAE 75W-140 extreme pressure API GL-5 gear lubricants are recommended.

**SUMMARY OF BENEFITS**

- Protects all types of gears including helical, spiral bevel and hypoid to minimise scuffing, welding or galling tooth wear in severe load applications
- Excellent resistance to foaming and corrosion
- Extreme pressure additives impart high load carrying capability
- Excellent viscosity characteristics enable high level wear protection over a wide range of operating temperatures and reduced drag at start up.
- Synthetic base oils provide outstanding thermal properties leading to cleaner gears and longer oil and equipment service life
- Advanced additive package does not corrode yellow metals such as copper and its alloys

**SPECIFICATIONS**

- SAE 75W-140
- API GL-5
- SAE 75W-140
- SAE J2360
- SUITABLE FOR USE IN DIFFERENTIALS FROM EATON, ROCKWELL AND OTHER MAJOR HEAVY DUTY MANUFACTURERS



ULTRA CLEAR GEAR LUBE LS 75W-140	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.863
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	172
@ 100°C	ASTM D445	cSt	27
VISCOSITY INDEX	ASTM D2270	-	195
POUR POINT	ASTM D97	°C	-39
FLASH POINT (COC)	ASTM D92	°C	170
COLOUR	ASTM D1500	-	<3

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

1LT - #301367

August 2022