

## DESCRIPTION

SNOW ARCTIC POWER 2 STROKE is an advanced, high performance, full synthetic engine lubricant designed to meet the special operating conditions of all 2 stroke Snowmobiles, All Terrain Vehicles, Utility Terrain Vehicles and other 2 stroke power equipment operating in severe conditions, especially in extreme cold environments. Compatible with leaded and unleaded gasolines, biofuels and other specialised fuels used in 2 stroke engines operating in harsh arctic conditions. SNOW ARCTIC POWER 2 STROKE will continue to flow and protect where ordinary oils will not flow or protect equipment. Note: Not suitable for use in outboard marine engines that call for a NMMA TCW 3. Please refer to manufacturer recommendations for correct mixing/blending ratio.

## SUMMARY OF BENEFITS

- Contains a diluent to aid mixing with fuel
- Low ash formulation controls piston, port and plug cleanliness
- Exceptionally low pour point, resists freezing and continues to flow in extreme cold
- Superior wear protection in all operating conditions
- Able to be used in all land based 2 Stroke equipment including Snowmobiles, Utility vehicles, motorcycles, chainsaws, lawn mowers and other 2 stroke powered equipment

## RECOMMENDATIONS

### SNOWMOBILES:

- Bombardier (BRP)
- Polaris
- Arctic Cat
- Yamaha

### LAWN MAINTENANCE/ FORESTRY EQUIPMENT:

- Hitachi
- Honda
- John Deere
- Kawasaki
- Lawn Boy
- Massey Ferguson
- Polaris
- Husqvarna
- Poulan

### POWERMATE (FORMERLY COLEMAN)

- Tecumseh
- Weedeater
- Woods
- Yamaha
- Yardman
- Stihl
- Dolmar

### SMALL CC MOTORCYCLES AND SCOOTERS:

- Yamaha
- TVS
- Bombardier (BRP)
- Honda
- Kawasaki

## SPECIFICATIONS

- API TC
- ISO-L-EGD
- JASO FD, FC
- TISI

## AVAILABLE PACK SIZES

#301389S - 1LT

SNOW ARCTIC POWER 2 STROKE	TEST METHOD	UNITS	RESULTS
DENSITY @ 30°C	ASTM D4052	kg/L	0.844
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	31.86
@ 100°C	ASTM D445	cSt	>6.5
VISCOSITY INDEX	ASTM D2270	-	145
COLOUR	VISUAL	-	BLUE
POUR POINT	ASTM D97	°C	-48
FLASH POINT (COC)	ASTM D92	°C	90
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	>1.1
SULPHATED ASH	ASTM D874	% mass	<0.1

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

## STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

December 2023