

**DESCRIPTION**

Racing 4T 100% Synthetic 5W-40 is formulated using premium synthetic base oils, synthetic PAO & Esters coupled with an effective additive package for the ultimate protection of motorcycle engines. Racing 4T with PAO & Ester demonstrates excellent performance in the face of the increasing demands of motorcycle engines. Racing 4T with PAO & Ester is dyed a fluorescent yellow colour for easy identification.

**SUMMARY OF BENEFITS**

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

**SPECIFICATIONS**

- SAE - 5W-40
- API - SN
- JASO - MA2

SAE VISCOSITY GRADE	5W-40
DENSITY, KG/L @ 15°C	0.855
COLOUR ASTM	Fluorescent Yellow
KINEMATIC VISCOSITY	
@ 40°C	87
@ 100°C	13.8
VISCOSITY INDEX	163
APPARENT VISCOSITY @ -30°C, cP	5900
POUR POINT °C	-42
FLASH POINT (COC) ,C	220
TBN, MG KOH/G	8.4

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

1LT - #301949