

DESCRIPTION

ALPHA ENGINE FLUSH OIL TREATMENT is a mixture of high flash point solvents and oil based detergents used to completely cleanse the interior of the engine from sludge, gum, rust and varnish

USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Compatible with all mineral, semi synthetic or fully synthetic motor oils.

DIRECTION

1. Before changing oil, pour the contents of one bottle in the crank case of the warm engine.
2. Let the engine run for a maximum of 10-15 minutes, alternatively at low and high rpm. In case of any irregular engine behaviour: switch off the engine immediately and proceed with step 3.
3. Drain the oil from the crank case.
4. Replace oil filter.
5. Refill crankcase with fresh motor oil as per manufacturer’s specifications.

DOSAGE

One bottle 300 ml bottle treats 4 to 6 litres of motor oil.

BENEFITS

- Internally cleans and flushes the engine with highly effective cleaning agents
- Eliminates gums, varnish and sludge
- Easily removes contaminants like carbon deposits, soot and liquids (water and fuel)
- Reduces fuel consumption and exhaust emissions by restoring engine condition and enabling the fresh oil to perform optimally

SPECIFICATIONS	RESULTS
APPEARANCE	AMBER LIQUID
ODOUR	OIL - SOLVENT
DENSITY @ 15°C	0.840
FLASH POINT	> 120°C

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Asia Pte Ltd.

AVAILABLE PACK SIZES

#330194



Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.