

TECHNICAL DATA SHEET

ALPHA DPF PLUS



DESCRIPTION

ALPHA DPF PLUS is an organo-metallic iron-based diesel fuel additive to be used as a catalyst for the regeneration of diesel particulate filters. ALPHA DPF PLUS lowers the ignition temperature of soot collected in the diesel particulate filter and optimizes periodic combustion of accumulated soot. The unique combination of a clean fuel system, clean combustion with lower emissions and catalysed soot particles will clean up and assist in keeping the DPF, catalytic converter, exhaust gas recirculation system (EGR) as well as the turbo charger and its variable geometry vanes clean from deposits.

USAGE

For all common passenger car diesel engines with standard or retrofitted diesel particulate filter (including common rail, turbo charged engines).

DIRECTION

Pour the contents of one bottle in the fuel tank before filling it with diesel fuel.

DOSAGE

One bottle 300 ml bottle treats 40 to 60 litres of diesel fuel.

BENEFITS

- Ensures trouble-free operation of your DPF-system
- Enables quick and complete soot combustion and regeneration
- Allows DPF to burn soot off at lower temperature and for shorter periods even in City/Stop-Start driving conditions
- Cleans the engine, the turbo variable vanes and exhaust system
- Reduces emission of smoke, HC, CO and particulate matter
- Improves fuel economy due to fewer and shorter regeneration cycles
- Extends DPF and catalyst service life
- Safe to use, non-flammable formula

SPECIFICATIONS	RESULTS
APPEARANCE	AMBER TO BROWN
ODOUR	CHARACTERISTIC/SOLVENT
DENSITY @ 15°C	0.791
FLASH POINT	> 61°C

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Asia Pte Ltd.

AVAILABLE PACK SIZES

#330234

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

July 2023

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au