

**DESCRIPTION**

Ultra Clear Gear Oil® 75W-85 is a high performance synthetic gear oil for modern manual transmissions. Ultra Clear Gear Oil® 75W-85 is recommended when SAE 75W or 80W are specified. It has the balance of viscosity and frictional properties, which ensure good shift feel and fast gear changes. This oil is ideal for modern 4, 5 and 6 speed manual gearboxes which need low viscosity oil for cold changing yet still need an SAE 85 when warm, to ensure quiet running. Ultra Clear Gear Oil® 75W-85 is also suited for use in differentials including limited slip differentials.

**SUMMARY OF BENEFITS**

- Ultra Clear Gear Oil® 75W-85 has a shear stable formulation, which exceeds the stringent 75W-85 requirements, ensuring full protection during extended drain intervals
- Naturally high viscosity index, stops cold shift baulking, yet still provides quiet running at operating temperature
- Reduces friction hence lowering operating temperature and frictional power losses
- Suitable for use in limited slip differentials

**SPECIFICATIONS**

- SAE VISCOSITY 75W-85
- API GL-5
- BORG WARNER 5M-42
- FORD ESP-M2C83-C
- MITSUBISHI ES-X-64021
- MB 235.31 (MEETS REQUIREMENTS)

**SUITABLE FOR**



ULTRA CLEAR GEAR OIL 75W-85	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.850
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	69
@ 100°C	ASTM D445	cSt	12.3
VISCOSITY INDEX	ASTM D2270	-	178
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°C	>200

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

205LT - #60050, 20LT - #62050