

DESCRIPTION

Outboard Four Stroke Oil is a synthetic high performance engine oil for use in water-cooled Fourstroke outboard motors calling for a 10W-40 API FC-W (CAT) specification. It is approved for API FC-W (CAT) requirements.

SUMMARY OF BENEFITS

- Suitable for FC-W (CAT) requirements
- Formulated using severely refined mineral oils to give excellent protection against engine wear for prolonged engine life

SPECIFICATIONS

- NMMA FC-W (CAT)
- API SM
- 10W-40 VISCOSITY
- JASO MA (T903:2006)

MEETS THE WARRANTY REQUIREMENTS OF: MERCURY, JOHNSON, EVINRUDE, YAMAHA, MARINER, FORCE, SUZUKI, TOHATSU AND ANY OTHER ENGINE REQUIRING FC-W PERFORMANCE

SUITABLE FOR



OUTBOARD FOUR STROKE	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.8610
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	100
@ 100°C	ASTM D445	cSt	15
TOTAL BASE NUMBER	FTIR	mgKOH/g	>5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

AVAILABLE PACK SIZES

205LT - #60082, 20L - #62082 and 4LT - #60482