

DESCRIPTION

ULTRA CLEAR LS 80W-90 is a fully synthetic ultra clear gear lubricant formulated for all cars, with and without "Limited Slip" differentials. The ULTRA CLEAR LS 80W-90 is blended from fully synthetic base stock, offering superior performance to that which can be offered by a mineral gear oil.

Note: ULTRA CLEAR LS 80W-90 is not approved for use in the differential of Commodore V8 and Holden 6 and 8 cylinder utilities which require a special GM H/BTR approved synthetic lubricant available from GMH dealers. ULTRA CLEAR LS 80W-90 can be used in differentials of Falcons with V8 engines.

SUMMARY OF BENEFITS

- ULTRA CLEAR LS 80W-90 synthetic formulation is more resistant to oil oxidation, giving longer drain intervals
- Excellent resistance heat degradation allows this grade to operate at higher temperatures than a mineral gear oil
- Naturally high viscosity index, reduces wear at start up yet still provides better protection at operating temperature
- Reduces friction hence lowering operating temperature and frictional power losses

SPECIFICATIONS

Ultra Clear Gear Oil meets the following international performance specifications:

- SAE Viscosity 80W-90
- MIL -L-2105D
- API Exceeds GL-5 (was classed GL-6 when this was a recognised

STORAGE INSTRUCTIONS

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TECHNICAL DATA SHEET

ULTRA CLEAR LS 80W-90



TYPICAL CHARACTERISTICS

ULTRA CLEAR LS 80W-90	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.859
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	185
@ 100°C	ASTM D445	cSt	18
VISCOSITY INDEX	ASTM D2270	-	135
POUR POINT	ASTM D97	°C	<-30
FLASH POINT, COC	ASTM D92	°C	228
COLOUR	ASTM D1500	-	1.5

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Head Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747
Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au