technical data sheet SYN-M 4T SAE 10W-40 PAO ESTER



SPECIFICATIONS

• SAE - 10W-40

• JASO - MA2

• API - SN

DESCRIPTION

Full synthetic SYN-M 4T SAE 10W-40 motorcycle engine oil is formulated using premium synthetic base oils and synthetic PAO, Esters coupled with an effective additive package for the ultimate protection of motorcycle engines. SYN-M 4T SAE 10W-40 motorcycle engine oil with Ester demonstrates excellent performance in the face of the increasing demands of motorcycle engines.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

SUITABLE FOR



SYN-M 4T SAE 10W-40	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D4052	kg/L	0.859
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	99.35
@ 100°C	ASTM D445	cSt	15.00
VISCOSITY INDEX	ASTM D2270	-	158
COLOUR	ASTM D1500	-	Natural
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°(226
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	7.8
APPARENT @-25 ° C,cP	ASTM D5293	сР	4989

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

GULF WESTERN PREMIUM QUALITY LUBRICATING OILS (AUST) PTY LTD

Office: 92-96 Links Road, St Marys NSW 2760 - PO BOX 515 Kingswood, NSW 2747 Phone: 02 9673 9600 - Fax: 02 9623 6466 - Email: sales@gulfwestern.com.au - Web: www.gulfwestern.com.au