

DESCRIPTION

Gulf Western Gear Lube is an extreme pressure, heavy duty lubricant recommended for hypoid or spiral bevel axles, gears and steering boxes of automotive equipment. Gulf Western Gear Lube is available in SAE viscosity grades 80W-90 and 85W-140.

SUMMARY OF BENEFITS

- Gulf Western Gear Lube protects all types of gears including helical, spiral bevel and hypoid to minimise scung, welding or galling tooth wear in severe load applications
- Excellent resistance to foaming and corrosion
- Extreme pressure additives impart high load carrying capacity to the oil
- Multigrade characteristics enable maintenance of wear protection over a wide range of operating temperatures and reduces drag at start up. The need for seasonal oil changes is eliminated
- Gear Lube may be used in a wide variety of manual transmissions and vehicle axles

SPECIFICATIONS

- SAE VISCOSITY 80W-90 & 85W-140
- API GL-4 AND GL-5
- MACK GO-H
- US MILITARY MIL-L-2105D/2106
- EATON
- ROCKWELL
- MB 235.20 (MEETS REQUIREMENTS)

SUITABLE FOR



GEAR LUBE	TEST METHOD	UNITS	80W-90	85W-140
DENSITY @ 15°C	ASTM D1298	kg/L	0.9042	0.9025
KINEMATIC VISCOSITY				
@ 40°C, mm ² /s	ASTM D445	cSt	151.94	319.6
@ 100 C, mm ² /s	ASTM D445	cSt	15.12	25
VISCOSITY INDEX	ASTM D2270	-	100	100
POUR POINT, °C	ASTM D97	°C	-30	-21
FLASH POINT, COC, °C	ASTM D92	°C	230	260
COLOR	ASTM D1500	-	2.5	3

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.