

DESCRIPTION

CHASSIS GREASE CH products are a range of high quality, general purpose greases suitable for a range lubrication applications. These adhesive and water resistant greases offer cost effective lubrication where application speed and temperatures are low to moderate.

CHASSIS GREASE CH products have a high resistance to water wash out and cling firmly to moving parts such as ball joints, chassis and U-joints and are suitable for use with manual lubrication or automated lubrication systems.

Suitable for a wide range of vehicular applications including tractors, trucks, earthmoving equipment and passenger vehicles.

SUMMARY OF BENEFITS

- Highly resistant to water wash off and providing high levels of corrosion resistance
- Allows effective lubrication even in damp environments
- Excellent clingability – stays put in application
- High mechanical stability – resists mechanical shearing offering longer lubricant life
- No heavy metals or other toxic or hazardous components
- Safe for use in applications where copper and its alloys (yellow metals) are used

SPECIFICATIONS

CHASSIS GREASE CH PRODUCTS MEETS THE FOLLOWING SPECIFICATIONS:

- NLGI GRADE 1, 2 AND 3 AS PER REQUIREMENT
- OPERATING TEMPERATURE RANGE: -10 TO 70°C

NLGI GRADE	1	2	3
Appearance	Green & Tacky	Green & Tacky	Green & Tacky
Worked Penetration @25°C, 1/10mm, 60 strokes	321	282	237
Dropping Point, °C	102	102	102
Rust Prevention	Pass	Pass	Pass
Copper Strip Corrosion	1b	1b	1b
Base Oil Viscosity at 100°C, cSt	20	20	20

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600