TECHNICAL DATA SHEET

RACING SYN-M 4T SAE 5W-40



DESCRIPTION

RACING SYN-M 4T 5W-40 is a 100% synthetic motorcycle oil formulated using premium synthetic base oils, with PAO and Esters, coupled with an effective additive package for the ultimate protection of motorcycle engines. Racing SYN-M 4T 5W40 with PAO and Ester demonstrates excellent performance in the face of the increasing demands of motorcycle engines, provides ultimate protection and performance reliability. Suitable for any type of high-performance motorcycle with 4-stroke engine for on-road and off-road riding. The premium synthetic base oils and advance additive system help to prolong the life of your engine.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

SPECIFICATIONS

- SAE 5W-40
- API SN
- JASO MA2

RACING SYN-M 4T	5W-40
DENSITY @ 15°C	0.855
KINEMATIC VISCOSITY	
@ 40°C	87
@ 100°C	13.8
VISCOSITY INDEX	163
COLOUR	Natural
POUR POINT	-42
FLASH POINT (COC),C	220
TBN, MG KOH/G	8.4
APPARENT VISCOSITY @ -30°C, cP	5900

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

July 2024