

DESCRIPTION

SCOOTER 4T SAE 10W-40 is formulated from premium base oils coupled with a highly effective additive package for the protection of scooter engines and optimal transmission operation. SCOOTER 4T SAE 10W-40 demonstrates excellent performance in the face of increasing demands of scooter engines. Suitable for use in 4-stroke scooter engines requiring an API SN (or earlier) and JASO MB oil.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear
- Correct frictional characteristics for operation in motorcycles with wet clutch
- Shear stable formulation offering enhanced protection across the full oil drain

SPECIFICATIONS

- SAE - 10W-40
- API - SN
- JASO - MB

TYPICAL CHARACTERISTICS

SCOOTER 4T SAE 10W-40	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D7042	kg/L	0.864
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	101
@ 100°C	ASTM D445	cSt	14.6
VISCOSITY INDEX	ASTM D2270	-	151
COLOUR	ASTM D1500	-	Natural
POUR POINT	ASTM D97	°C	-39
FLASH POINT (COC)	ASTM D92	°C	216
Total Base Number	ASTM D2896	mgKOH/g	6.56
APPARENT VISCOSITY @ -25°C	ASTM D5293	cP	6073

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.