

TECHNICAL DATA SHEET

TRANSYN-MF ATF



DESCRIPTION

Transyn-MF is a synthetic blend multi functional Automatic Transmission Fluid. It meets the requirements of a wide range of American, Japanese and European OEM's.

Transyn-MF is a mid-tier ATF and does not meet some of the OEM requirements of SYN-TS, most notably 6 Speed ZF transmissions that require a fluid meeting ZF-TE-ML-09.

Note: The below is a summary only, for more details please contact Gulf Western Oil Technical.

SUMMARY OF BENEFITS

- Synthetic blend
- Suitable for extended drain intervals where standard Dexron III mineral oils are required
- Reduces the need to stock additional fluids
- Friction modified formulation
- High VI, Shear stable blend that offers excellent cold start properties
- Ideal for heavy duty applications such as towing and long distance driving in very hot or cold climates
- Can be used where a Dexron IID, III, IIIE, VI, Ford 95LE, ATF+4, SPIII and C4 fluids are called for

SPECIFICATIONS

Transyn-MF ATF meets the following international performance specifications:

- Dexron III
- ATF+3,+4
- ATF JWS 3309
- Allison TES295, 389
- Chrysler AS68RC, SP-III
- Mercedes Benz 236.1, 236.11, 236.12, 236.14, 236.15, 236.3, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9 & 236.91
- Ford WSS-M2C922-A1
- TYPE A Suffix
- Honda DW-1, Z-1
- Hyundai/Kia Genuine, 1K, JWS 3309, NWS 9638 T-5
- Isuzu Genuine ATF
- Jaguar Fluid 8432, JLM 20238, 20292, 21044, K17
- Land Rover TYK500050
- MAN 339A
- Maserati 231603
- Mazda F1, FZ, JWS3317, M5, MIII, T-IV
- Mitsubishi J2, J3, SPII/III
- Nissan Matic D, J, K, S, W
- Porsche 043 204 41, 205 09, 205 28, 304 00, 999 917 547 00 (A2)
- Renault Matic D2
- SAAB 3309 T-IV, 93 165 147 – AW1
- Subaru HP
- Suzuki 3314, 3317
- Toyota/Lexus DII, T, T-III, T IV
- VW/Audi 052 – 025A2, 055, 162, 533, 990, 055 005, 025, 540, 000 162
- Volvo PN 1161521, 1161540/1161640
- ZF TE-ML 11A, TE-ML-11B

STORAGE INSTRUCTIONS

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

HEALTH, SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

TECHNICAL DATA SHEET

TRANSYN-MF ATF



TYPICAL CHARACTERISTICS

TRANSYN-MF ATF	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D1298	kg/L	0.855
KINEMATIC VISCOSITY @ 40°C	ASTM D445	cSt	31
@ 100°C	ASTM D445	cSt	6.4
VISCOSITY INDEX	ASTM D2270	-	165
POUR POINT	ASTM D97	°C	-42
FLASH POINT (COC)	ASTM D92	°C	224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

AVAILABLE PACK SIZES

205lt - 60058, 60lt - 66058, 20lt - 62058