

**DESCRIPTION**

TWO STROKE - AIR COOLED Oil is a Full Synthetic engine oil meeting the demand of modern engines and suitable for E-TEC technology engine; High performance low ash oil for Air-Cooled 2-stroke motors formulated for both oil injected and pre-mixed systems. Recommended for 2-stroke lawnmowers, chainsaws, brush cutters, motorbikes, and other similar 2-stroke applications. TWO STROKE - AIR COOLED meets the requirement of the full range of low ash 2-stroke oil specifications from JASO FB and ISO-L-EGB to JASO FD & ISO-L-EGD quality levels.

Note: Not suitable for use in outboard marine engines that call for a NMMA TCW 3. Please refer to manufacturer recommendations for correct mixing/blending.

**SUMMARY OF BENEFITS**

- Suitable for API TA, TB, TC requirements
- Low ash formulation controls piston, port and plug cleanliness
- Contains a diluent to aid mixing with leaded and unleaded petrol
- Synthetic formulation

**SPECIFICATIONS**

- API TC, TB, TA
- JASO FD, FC, FB
- ISO-L-EGD
- TISI

**RECOMMENDATIONS**

Snowmobiles:	Lawn Maintenance/ Forestry Equipment:	Powermate (formerly Coleman):	Small CC Motorcycles and Scooters:
<ul style="list-style-type: none"> <li>• Bombardier (BRP)</li> <li>• Polaris</li> <li>• Arctic Cat</li> <li>• Yamaha</li> </ul>	<ul style="list-style-type: none"> <li>• Stihl</li> <li>• Husqvarna</li> <li>• Hitachi Honda</li> <li>• John Deere</li> <li>• Kawasaki</li> <li>• Lawn Boy</li> <li>• Massey Ferguson</li> <li>• Polaris</li> <li>• Poulan</li> </ul>	<ul style="list-style-type: none"> <li>• Tecumseh</li> <li>• Weedeater</li> <li>• Woods</li> <li>• Yamaha</li> <li>• Yardman</li> <li>• Stihl</li> <li>• Dolmar</li> </ul>	<ul style="list-style-type: none"> <li>• Yamaha</li> <li>• TVS</li> <li>• Bombardier (BRP)</li> <li>• Honda</li> <li>• Kawasaki</li> </ul>

**SUITABLE FOR**



TWO STROKE - AIR COOLED	TEST METHOD	UNITS	RESULTS
DENSITY @ 30°C	ASTM D1298	kg/L	0.833
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	36.93
@ 100°C	ASTM D445	cSt	7.08
VISCOSITY INDEX	ASTM D2270	-	154
POUR POINT	ASTM D97	°C	-30
FLASH POINT (COC)	ASTM D92	°C	90
TOTAL BASE NUMBER (TBN)	ASTM D2896	Mg KOH/g	>1.13
SULPHATED ASH	ASTM D874	% mass	0.095
COLOUR, ASTM	ASTM D1500	-	GREEN

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.*

**STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

**AVAILABLE PACK SIZES**

4LT - # 304268SD, 1LT - #301268SD

May 2024