

DESCRIPTION

Racing Syn-M 4T SAE 10W-50 100% synthetic is formulated using premium synthetic base oils, synthetic PAO & Esters coupled with an effective additive package for the ultimate protection of motorcycle engines. Racing Syn-M 4T SAE 10W-50 100% synthetic demonstrates excellent performance in the face of the increasing demands of motorcycle engines.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

SPECIFICATIONS

- SAE - 10W-50
- API - SN
- JASO - MA2

TYPICAL CHARACTERISTICS

RACING SYN-M 4T 10W-50	TEST METHOD	UNITS	RESULTS
DENSITY @ 15°C	ASTM D4052	kg/L	0.8570
KINEMATIC VISCOSITY			
@ 40°C	ASTM D445	cSt	122.50
@ 100°C	ASTM D445	cSt	18.67
VISCOSITY INDEX	ASTM D2270	-	172
COLOUR	ASTM D1500	-	Natural
POUR POINT	ASTM D97	°C	-39
FLASH POINT (COC)	ASTM D92	°C	230
TOTAL BASE NUMBER	ASTM D2896	mgKOH/g	6.68
APPARENT @-25 ° C,cP	ASTM D5293	cP	3677

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.