TECHNICAL DATA SHEET

RACING SYN-M 4T SAE 10W-50



DESCRIPTION

Racing Syn-M 4T SAE 10W-50 100% synthetic is formulated using premium synthetic base oils, synthetic PAO & Esters coupled with an effective additive package for the ultimate protection of motorcycle engines. Racing Syn-M 4T SAE 10W-50 100% synthetic demonstrates excellent performance in the face of the increasing demands of motorcycle engines.

SUMMARY OF BENEFITS

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

SPECIFICATIONS

- SAE 10W-50
- API SN
- JASO MA2

RACING SYN-M 4T	10W-50
DENSITY @ 15°C	0.854
KINEMATIC VISCOSITY	
@ 40°C	124.4
@ 100°C	18.85
VISCOSITY INDEX	171
COLOUR ASTM	<2.5
POUR POINT	-36
FLASH POINT (COC),C	220
TBN, MG KOH/G	6.6
APPARENT VISCOSITY @ -25°C, CP	4200
APPEARANCE	CLEAR AND BRIGHT LIQUID WITH STRAWBERRY FRAGRANCE

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

Sep 2024