# TECHNICAL DATA SHEET

# SYM-M 4T SAE 10W-40



## **DESCRIPTION**

Full synthetic SYN-M 4T SAE 10W-40 motorcycle engine oil is formulated using premium synthetic base oils and synthetic PAO, Esters coupled with an effective additive package for the ultimate protection of motorcycle engines. SYN-M 4T SAE 10W-40 motorcycle engine oil with Ester demonstrates excellent performance in the face of the increasing demands of motorcycle engines.

#### **SUMMARY OF BENEFITS**

- Excellent resistance to high temperature thermal breakdown
- Excellent anti-sludge properties
- Excellent engine cleanliness
- Resists foaming to protect against rust, corrosion and wear

## **SPECIFICATIONS**

- SAE 10W-40
- API SN
- JASO MA2

#### **SUITABLE FOR**



SYM-M 4T SAE	10W-40
DENSITY @ 15°C	0.8575
KINEMATIC VISCOSITY	
@ 40°C	96.14
@ 100°C	14.39
VISCOSITY INDEX	155
COLOUR	Natural
POUR POINT	-39
FLASH POINT (COC),C	220
TBN, MG KOH/G	6.55
APPARENT VISCOSITY @ -30°C, cP	5104

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

## STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

Oct 2024