

DESCRIPTION

AGRITRANS UTTF LOW VIS is a multipurpose oil suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches, and brakes. The anti-squawk additive ensures effective operation of wet brakes. AGRITRANS UTTF LOW VIS has been specifically developed to meet a wide range of specifications from most modern tractor and hydraulic pump OEMs. Gulf Western's additive technology has been field tested in over 250 tractors and that combines to more than 200,000 hours of field tests.

SUMMARY OF BENEFITS

- Superior gear wear protection
- Correct frictional characteristics ensure quiet wet brake operation
- Proven field performance
- Good anti-foam characteristics
- Excellent shear stability and thermal/oxidation stability provide long fluid life
- Good water tolerance ensures hydraulic performance is maintained
- Low copper activity
- Good filterability
- Excellent anti-squawk properties

SPECIFICATIONS

- API GL-4
- SAE 10W-30 (TABLE J300)
- SAE 80W (TABLE J306)
- JOHN DEERE J20C
- FORD/NEW HOLLAND ESN-M2C134-D, FNHA-2-C-200.00, FNHA 2-C-201.00
- CNH MAT 3540, 3525, 3505
- JI-CASE MS 1206, 1204, 1207, 1210
- INTERNATIONAL HARVESTER B5-B6
- STEIGER
- VERSATILE
- DEUTZ-ALLIS 272843, 257541, 246634
- FIAT
- KUBOTA UDT
- MASSEY FERGUSON M-1110, 1127A/B, 1129A, 1135, 1141, 1143, 1145
- ALLIS-CHALMERS POWER FLUID 821
- ALLISON C4
- CAT TO-2
- ZF TE-ML 03E, 03F, 05F, 06K
- AGCO 821XL
- WHITE Q1826, 1705, 1802, 1826, 1766, 1722, 1766B, TYPE 55

SUITABLE FOR



AGRITRANS UTTF LOW VIS	TEST METHOD	VALUE
DENSITY @ 15°C	ASTM D-4052	0.8685
KINEMATIC VISCOSITY		
@ 40°C, mm ² /s		36.43
@ 100 °C, mm ² /s	ASTM D445	7.77
POUR POINT °C	ASTM D97	-45
FLASH POINT, °C	ASTM D92	200
VISCOSITY INDEX	ASTM D2270	192
TBN	ASTM D2896	10

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

STORAGE INSTRUCTIONS & HEALTH, SAFETY AND ENVIRONMENT INFORMATION

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C. Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Oil on: 02 9673 9600.

Mar 2025